

EXILE's new Spyder II computer-to-screen printer provides the ultimate in quality, while simplifying the process of creating screen masks. This high-resolution device can image screens at over 2 square feet per minute for extremely fast throughput. Perfect for the busy screen room, the Spyder II can help eliminate film, improve print quality, reduce labor, and speed up job turnaround.

The background of the entire page is a grayscale photograph of a person's hand operating a screen printing machine. An orange rectangular overlay is positioned in the lower half of the image, containing white text. The text is arranged in a header, a bulleted list, and a paragraph. The overall design is clean and professional, emphasizing the industrial nature of the product.

## INCREASED SPEED MEANS

- BETTER MECHANICAL & PRODUCTION EFFICIENCY
- IMPROVED PRINT QUALITY
- ENHANCED DOT PLACEMENT

The Spyder II has a streamlined interface with easy-to-use touch screen controls. The Spyder II is your all-in-one machine providing a simplified structure, improved performance, control, and long-term reliability. By using heated wax ink with phase change inkjet head technology, high-density images are placed directly onto a coated screen.

# FAST & ACCURATE RESULTS



The Spyder II 30 supports standard frames up to 30" x 40", while the larger Spyder II 52 supports frame sizes up to 54" x 46". A full-featured Harlequin RIP is included to provide a fast and reliable file output. The Spyder II also accepts 1-bit tiff files from any other RIP to easily fit into an existing pre-press workflow.

- BI-DIRECTIONAL PRINTING
- ELIMINATES FILM
- REDUCED LABOR COSTS
- PRECISION PLACEMENT
- FASTER PRESS SETUP
- IMPROVED QUALITY
- REDUCED EXPOSURE TIMES

## EQUIPMENT SPECIFICATIONS

Model	Spyder II Computer-to-Screen system
Technology	Phase-change inkjet / Solid ink
Resolution	600 dpi
Halftone Capability	75 lpi @ 600 dpi
Imaging Speed	Approximately 2.4 sq ft/min (13 sq m/h) @ 600 dpi
Accuracy	.001" from screen to screen
Power Requirements	120v/220v 50-60 HZ 15 amp
Compressed Air	Required
Network	Ethernet
Operating Temperature	50°F to 86°F / 10°C to 30°C
Operating Humidity	35% to 75% non-condensing
Ink Type	Solid block / Water dispersable photo resist mask

MODEL	SPYDER II DTS 30	SPYDER II DTS 52
Max Media Size	30 in x 40 in (76 cm x 101 cm)	54 in x 46 in (137 cm x 116 cm)
Max Image Size	25 in x 30 in (63 cm x 76 cm)	50 in x 40 in (127 cm x 102 cm)
Dimensions	32 in x 49 in x 61 in (79 cm x 124 cm x 155 cm)	32 in x 80 in x 61 in (79 cm x 203 cm x 155 cm)
Weight	Weight 300 lbs (136 kg) 340 lbs (150 kg)	340 lbs (150 kg)

## RIP SPECIFICATIONS

RIP Type	RTI Harlequin RIP
Platform: PC	Mac and PC available
Screening	AM and FM (stochastic) screening available
Input File Formats	Postscript III, PDF, EPS, TIFF
RIP Options	Auto Trapping, Color Management / Proofing, Hybrid Screening

Backing the system is EXILE's outstanding service and support. Whether onsite or over the phone or web, our technicians are sure to keep you printing smoothly and efficiently. Contact us to find out more about the Spyder II DTS.



**EXILETECH.COM**

### EXILE TECHNOLOGIES

7007 Pinemont Drive  
Houston, TX 77040

[info@exiletech.com](mailto:info@exiletech.com)

TOLL FREE: 800.747.7651

P: 713.343.5662

### EXILE TECHNOLOGIES LTD

F3 Bramingham Business Park  
Enterprise Way, Luton  
Bedfordshire LU3 4B, England

[info@exiletech.co.uk](mailto:info@exiletech.co.uk)  
+44-1-582-573980



# SPYDER II

COMPUTER-TO-SCREEN SYSTEM



**EXILE**  
TECHNOLOGIES